

HOOD Equipment 45000 Series Industry Leading Heavy Duty Loader Achieving Incredible Results







The Hood 45000 Series loaders provide you unprecedented results for any material handling challenge. The 45000 is widely regarded an excellent choice for the forestry, pipe line, and construction industries. It is also an efficient loader for recycling and refuse clean-up applications.



45000 Series Industry Leading Heavy Duty Loader

Market Leader

Highest Capacity in the Industry

AKM Series

Unrivaled Stability

Hood Equipment, Inc. P.O. Box 307 Iron River, WI 54847 715-372-4222

Specifications

Lift Capacity

• 38,500 lbs @ 10' radius

Booms

- · standard boom length 36 feet
- high tensile alloy hinge pins within manganese bronze bushings
- · engineering requests longer boom lengths available

Outriggers

- · 24" square pivoting pad size
- 7" bore x 20.5" stroke x 3.5" rod cylinders
- automatic cylinder load locks for maximizing stability on uneven terrain

Swing System

- 360 degrees continuous rotation
- dual hydraulic motor with failsafe brake-powered planetary gearboxes driving internal tooth 53" turntable
- · bearing brakes rated for 600,000 loads

Subframe

- heavy duty 24" deep H beam design using high tensile steel
- sub-frame weldment with integral stabilizer housings and fenders
- unmatched machine-leveling capability under virtually any conditions

Engine

- John Deere: 6.8L Final Tier IV, 200 HP @ 2200 RPM
- automatic engine shutdown system controlled by engine coolant and oil pressure
- 155 gallon diesel fuel tank

Hydraulic System

- main cylinder: two 6" bore x 48" stroke x 3.5" rod-fabricated heavy wall tubing barrel
- knuckle cylinder: 7" bore x 48" stroke x 3.5" rod-fabricated heavy wall tubing barrel
- hydraulic joystick servo system
- 120 gallon oil reservoir with dual 9 micron return filters
- variable displacement piston pumps for the main and knuckle functions
- vane hydraulic pumps for the swing, servo, and other functions
- deluxe cab: 50" wide x 60" long with a comfortable ultraadjustable seat with joysticks in armrests

Options

- hydraulically actuated cab platform up to 42" height
- self propelled carrier: 4 x 4 axels wheel drive
- · stationary heel racks and full-powered live heels