

# S-182 Series High Capacity Industry Leading Loader

Dependable | Custom | American-Made







The Hood S-182 Series loaders meet any material-handling challenge. Their performance has been widely proven in the forestry, pipeline, and construction industries. The S-182 is also an efficient loader for recycling and refuse clean-up applications.



## S-182 Series High Capacity Industry Leading Loader

## Industry Leader

## Highest Capacity

### Multiple Mounting Options:

- trailer mount
- truck mount
- self-propelled carriers
- electric mount

Hood Equipment, Inc. P.O. Box 307 Iron River, WI 54847 715-372-4222

## Specifications

#### **Lift Capacity**

• 18,500 lbs @ 10' Radius

#### Booms

- · standard boom length 30 feet
- high tensile alloy hinge pins within manganese bronze bushings
- · engineering requests longer boom lengths available

#### Outriggers

- · 18" or 24" square pivoting pad size
- · 6" bore x 24" stroke x 3" rod cylinders
- automatic cylinder load locks for maximizing stability on uneven terrain

#### **Swing System**

- 360 degrees continuous rotation
- dual hydraulic motor with failsafe brake powered planetary gearboxes driving internal tooth 39" turntable bearing brakes rated for 600,000 loads

#### Subframe

- · heavy duty 16" deep H beam design high tensile steel
- sub-frame weldment with integral stabilizer housings and fenders
- unmatched machine leveling capability under virtually any conditions

#### **Engine**

- John Deere: 6.8L Final Tier IV, 200 HP @ 2200 RPM
- automatic engine shutdown system controlled by engine coolant and oil pressure
- 130 gallon diesel fuel tank

#### **Hydraulic System**

- main cylinder: 7" bore x 42" stroke x 3.5 rod fabricated heavy wall tubing barrel
- knuckle cylinder: 7" bore x 30" stroke x 3.5 rod fabricated heavy wall tubing barrel
- · hydraulic joystick servo system
- 120 gallon oil reservoir with dual 9 micron return filters
- three vane hydraulic pumps providing a total flow of 150 GPM
- · individual pumps for the main, knuckle and swing functions
- · one 10 GPM pump for auxiliary and servo functions
- deluxe cab 38" wide x 60" long with a comfortable ultraadjustable seat with joysticks in armrests

#### **Options**

- · hydraulically actuated cab platform up to 42" height
- · trailer type carrier
- self propelled carrier 4 x 4 axels wheel drive
- rough terrain self propelled carrier 6 x 6 axels wheel drive
- · stationary heel racks and full powered live heels